

NAME

downtimed – system downtime monitoring and reporting daemon

SYNOPSIS

```
downtimed [ -D ] [ -d datadir ] [ -f timefmt ] [ -l log ] [ -p pidfile ] [ -S ] [ -s sleep ]
downtimed -v
```

DESCRIPTION

The **downtimed** daemon waits in the background, frequently updating a time stamp file on the disk. If the daemon is killed with a signal associated with a normal system shutdown procedure, it will record the shutdown time on the disk.

When the daemon is restarted during the next boot process, it will report how long the system was down and whether it was properly shut down or crashed. The downtime report is output to the system log or to a specified log file. Also a record is appended to the downtime database.

OPTIONS

- D** Do not create nor update the downtime database.
- d** *datadir*
The directory where the time stamp files as well as the downtime database are located. The default directory is determined at compile time.
- f** *timefmt*
Specify the time and date format to use when reporting using **strftime(3)** syntax. The default is "%F %T".
- l** *log* Logging destination. If the argument contains a slash (/) it is interpreted to be a path name to a log file, which will be created if it does not exist already. Otherwise it is interpreted as a syslog facility name. The default logging destination is "daemon" which means that the messages are written to syslog with the daemon facility code.
- p** *pidfile*
The location of the file which keeps track of the process ID of the running daemon process. The system default location is determined at compile time.
- S** Normally **fsync(2)** is performed after each update of the time stamp. This option disables the **fsync(2)**. It reduces the load on the disk system but makes the downtime measurement less reliable.
- s** *sleep*
Defines how long to sleep between each update of the on-disk time stamp file. More frequent updates result in more accurate downtime reporting in the case of a system crash. Less frequent updates decrease the amount of disk writes performed. The default is to sleep 15 seconds between each update. If you are using a flash memory based SSD or other disk which has limited amount of write cycles per block, it might be a good idea to set the sleep time to a higher value to prolong the lifetime of the storage device.
- v** Display the program version number, copyright message and the default settings.

SIGNALS**SIGHUP**

Close and re-open the output log. Use in case you want to rotate the log file.

SIGTERM and SIGINT

Terminate gracefully. These signals signify that a graceful system shutdown is in process.

EXIT STATUS

The daemon exits 0 on success, and >0 if an error occurs.

SEE ALSO

downtimes(1), **syslog.conf(5)**, <http://dist.epipe.com/downtimed/>

BUGS

The reporting accuracy in case of a system crash depends on how often the time stamp is updated.

Finding out the system startup time is very operating system specific. If the program does not have specific code to support your operating system, it assumes that the system started when the daemon started.

Reporting is inaccurate if the system clock changes during system downtime or startup process. Daylight saving time changes have no effect as all calculations are done using UTC.

COPYRIGHT

Copyright © 2009–2013 EPIPE Communications. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The views and conclusions contained in the software and documentation are those of the authors and should not be interpreted as representing official policies, either expressed or implied, of EPIPE Communications.